



Strength tested
by
BUET



MATADOR

uPVC PIPE & FITTINGS

strong & glossy...

www.matador.com.bd

MATADOR

uPVC PIPE & FITTINGS

strong & glossy...



uPVC পাইপ এবং ফিটিংস্‌ ক্রয়ে করনীয়

- . মূল্য নয় পণ্যই প্রথম বিবেচনায় রাখুন
- . কারো প্ররোচনায় নয় নিজেই পরীক্ষা করে বুঝে নিন
- . দেখে নিন এর থিকনেস, স্ট্রেংথ, ফিনিসিং ও গুনগত মান দীর্ঘস্থায়ী ব্যবহারের উপযোগী কিনা
- . প্রয়োজনে বাজারে প্রাপ্ত প্রতিটি পাইপ এবং ফিটিংস্‌ একত্রিত করে তুলনা করুন - অতঃপর ক্রয় করুন।

MATADOR uPVC ফিটিংস্‌

বাজারে প্রাপ্ত সকল ফিটিংস্‌ থেকে আলাদা কারন ইহা :

- . স্ট্রেং এবং গ্লসি
- . স্ট্রেংথ টেস্ট বুয়েট হতে পরীক্ষিত
- . উৎকৃষ্ট কাঁচামাল দ্বারা তৈরী তাই দীর্ঘস্থায়ী ব্যবহারের নিশ্চয়তা
- . বি-গ্রেড, স্পেসাল বা স্ট্যান্ডার্ড বলে বিকল্প কোন ফিটিংস্‌ নেই।



MATADOR

uPVC FITTINGS
for Soil, Waste & Vent (SWV) Systems

BENDs



Plain Bend **FF**



Back Door Bend **FF**



Side Door Bend **FF**



45 deg Bend **FF**



45 deg Bend **MF**



Off-set Bend **MF**

TEEs



Plain Tee **FF**



Back Door Tee **FF**



Right Door Tee **FF**



Left Door Tee **FF**



Cross Tee **FF**



Cross Door Tee **FF**

Strength tested by
BUET



MATADOR

uPVC FITTINGS
for Soil, Waste & Vent (SWV) Systems

BENDs



Plain Band-1.25", 1.5", 2"



Plain Band-4"



Plain Band-6"



45 deg band-1.25", 1.5", 2"



45 deg band-4"



45 deg band-6"

TEEs




Plain Tee-1.25", 1.5", 2"



Plain Tee-4"



Plain Tee-6"



Short Trap-4"



4"x2" Reducing Door Tee



6"x4" Reducing Door Tee

Strength tested by
BUET



MATADOR

uPVC FITTINGS
for Soil, Waste & Vent (SWV) Systems

TRAPs



U-Trap Body MF



Long Trap FF



S-Trap MF

WYEs



45 deg Wye FF



4/2 Reducing Wye FF



6/4 Reducing Wye FF

Accessories



Vent Cowl



Socket



Reducing Bush



Pipe Clip



Solvent Cement (P & S)



Solvent Cement (VICPLAS)

Strength tested by
BUET



MATADOR

BATHROOM ACCESSORIES
Elegant Bathroom Fittings

Bathroom Accessories



Topaz Classic Tissue Holder



Emerald Tissue Holder



Opal Soap Case



Topaz Soap Case



Regular Soap Case



Zircon Towel Rail



Push Shower Splash



Push Shower Euro Slim



Connection Pipe



Magic Pipe-1.25'' & 1.5''




BIB Cock Ultra



BIB Cock Jet Flow

Strength tested by
BUET


uPVC PIPE



SWR- Pipe



BS- Pipe



Thread- Pipe



BIB Cock Classic



Sink Cock Classic



Basin Cock Glory



Angle Cock Classic



MATADOR uPVC PIPE & FITTINGS for Soil, Waste & Vent (SWV) Systems

uPVC Pipe With Specifications
ISO 4422: 1996(E)

Nominal O.D (mm)	Nominal Wall Thickness (mm)				
	PN 6.3	PN 8	PN 10	PN 12.5	PN 16
32			1.6	1.9	2.4
40	1.5	1.6	1.9	2.4	3.0
50	1.6	2.0	2.4	3.0	3.7
63	2.0	2.5	3.0	3.8	4.7
75	2.3	2.9	3.6	4.5	5.6
110	2.7	3.4	4.2	5.3	6.6
140	3.5	4.3	5.4	6.7	8.3
160	4.0	4.9	6.2	7.7	9.5
200	4.9	6.2	7.7	9.6	11.9
225	5.5	6.9	8.6	10.8	13.4
250	6.2	7.7	9.6	11.9	14.8
315	7.7	9.7	12.1	15.0	18.7
355	8.7	10.9	13.6	16.9	21.1
400	9.8	12.3	15.3	19.1	23.7

uPVC Pressure Pipe
In Accordance to BS 3505: 1968

Nominal Size	OuterDia (mm)		Class B (6 bar)		Class C (9 bar)		Class D (12 bar)		Class E (15 bar)		Class 7 (22-40 bar)	
Inch	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
1/2	21.2	21.5							1.7	2.1	3.7	4.3
3/4	26.6	26.9							1.9	2.5	3.9	4.5
1	33.4	33.7							2.2	2.7	4.5	5.2
1.1/4	42.1	42.4					2.2	2.7	2.7	3.2	4.8	5.5
1.1/2	48.1	48.4					2.5	3.0	3.1	3.7	5.1	5.9
2	60.2	60.5			2.5	3.0	3.1	3.7	3.9	4.5	5.5	6.3
3	88.7	89.1	2.9	3.4	3.5	4.1	4.6	5.3	5.7	6.6		
4	114.1	114.5	3.4	4.0	4.5	5.2	6.0	6.9	7.3	8.4		
5	140.0	140.4	3.8	4.4	5.5	6.4	7.3	8.4	9.0	10.4		
6	168.0	168.5	4.5	5.2	6.6	7.6	8.8	10.2	10.8	12.5		
8	218.8	219.4	5.3	6.1	7.8	9.0	10.3	11.9	12.6	14.5		
10	272.6	273.4	6.6	7.6	9.7	11.2	12.8	14.8	15.7	18.1		
12	323.4	324.3	7.8	9.0	11.5	13.3	15.2	17.5	18.7	21.6		
14	355.0	356.0	8.5	9.8	12.6	14.5	16.7	19.2	20.5	23.6		
16	405.9	406.9	9.7	11.2	14.5	16.7	19.0	21.9	23.4	27.0		
18	456.7	557.7	11.0	12.7	16.3	18.8	21.4	24.6				

Strength tested by
BUET



MATADOR GROUP, a leading plastic products manufacturing Industry of Bangladesh, involved in making toothbrushes, ballpoint pens, combs, razors etc. for the last 35 years, is now making world class uPVC fittings for soil, waste and vent (SWV) systems for the first time in Bangladesh.

Since independence in 1971, a good number of Industries in Bangladesh were seen to be involved in manufacturing PVC pipes. uPVC fittings which are vital components of SWV systems, are however left out to be imported by some pipe manufacturers as well as by some commercial importers. In the result, huge amount of foreign exchange is drained out.

The question as to why uPVC fittings are imported at the cost of huge amount of foreign exchange remained yet to be answered. In an honest endeavour to search for the answer and to fill-in the gap hitherto existing, Matador Group came into being and took up the task of making uPVC fittings in Bangladesh.

Pipe &

Matador uPVC fittings are made by state-of-the-art machineries with high quality raw materials imported from Singapore under technical assistance provided by Singapore Polymer Corporation (PTE) Ltd., Singapore.

A highly skilled & well-trained production team of Matador is committed to ensure dimensional accuracy, flawless & glossy finishing of all the fittings. In selecting raw materials, care and caution is taken to ensure proper strength, durability & stability of the fittings. The fittings are subjected to several physical & chemical tests at the Mechanical Engineering Department of BUET. The test results revealed that Matador uPVC fittings have sufficient strength to withstand internal or external pressure while applied to the SWV systems.

Matador uPVC fittings are heavy, strong, glossy and durable for at least 50 years.

For proper bonding of uPVC fittings with pipes, it is important to use the right Solvent Cement. Matador is offering P&S and VICPLAS brand Solvent Cements, imported from Singapore, for providing assistance to the plumbers in fixing the pipes with fittings.

Matador Polyfit Industries

Corporate Office: Matador Harbour
102, Azimpur Road, Dhaka-1205
Phone: 9677782, 58612674
Fax: 880 2 8627909